

Surface Preparation

Masonry, brick, stone, clay tile and concrete patio surfaces must be clean and free of surface contaminants.

New masonry, stucco and concrete must be cured for a minimum of 30 days.

Application and Clean-up

Do not apply when air or surface temperature is below 40°F or may fall below 40°F for 24 hours after application. Shake container thoroughly before using. Do not thin or combine with any other products. Apply liberally and evenly using a low-pressure sprayer, or a nylon or synthetic brush. A low-pressure sprayer is a simple and easy method to apply this product. When using a sprayer, be sure to back-brush or roll immediately after spraying to ensure a uniform application and color distribution. To avoid streaking when spraying vertical surfaces, start at the bottom and spray toward the top. Apply only as much McCloskey Waterproofing Sealer as the surface will absorb. Redistribute any excess sealer that has dripped or does not penetrate into the surface after 10 minutes. One coat is recommended. Reapply seasonally or every 1 – 2 years depending on exposure. Use caution when standing or walking on surfaces still wet after the application of Waterproofing as the surface may be very slippery. To stain or paint over surfaces treated with McCloskey Waterproofing Sealer, allow a period of up to 12 months for the surface to sufficiently weather, and always test several areas to ensure penetration and adhesion of stain or paint. Do not use steel wool on surfaces that are to be coated with this product. Do not apply over painted or sealed surfaces. Clean brushes and equipment with soap and water.

Cautions (7980)

WARNING: May be harmful if swallowed. May be irritating to eyes and skin. When spraying, avoid breathing vapors – use only in areas of adequate ventilation. Wear splash-proof goggles during spray applications. If you experience eye watering, headaches or dizziness, increase fresh air or leave the area. Keep container closed when not in use.

FIRST AID: IF SWALLOWED: GIVE LARGE QUANTITIES OF WATER. DO NOT INDUCE VOMITING. **CALL PHYSICIAN IMMEDIATELY.** EYES: Flush eyes immediately with water for 15 minutes. **Call physician.** SKIN: Wash thoroughly with soap and water. Remove contaminated clothing. **Call physician if irritation persists.**

**DO NOT TAKE INTERNALLY.
KEEP OUT OF REACH OF CHILDREN.**
For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

**EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732**

This product contains less than 100 g/L VOC

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean-up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The data on this sheet represents typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product, is the replacement of the defective product, or a refund of its purchase price, at our option.